

CELO

FORCE ONE



105
Joule



3,6Kg
Compact
tool



100%
Balancing

The powerful, lightweight and ergonomic gas nailer

Japanese Technology

CE

Gas nailer

FORCE ONE

**The best gas nailer in its class
- with extensive range of accessories**



Main features / Advantages



Powerful

Setting energy of 105 Joule for high fastening quality [steel thickness up to 5 mm]



Constant power

Consistent gas injection regardless of temperature



Long lasting battery

up to 4500 fastenings per charge



Versatile

nails from 13 to 38 mm length for many different applications



Short contact pressure

enables fatigue-free working, especially with overhead installation



Quick

up to 2.5 nails per second



Good accessibility

even in narrow places due to the slim design and the extended nose



3,6 kg

Lightweight

with only 3,6 kg including battery the FORCE ONE is the lightest gas nailer in its class




Highly effective dust protection

Clever filter systems at the suction and discharge openings




Ergonomic handle

relieves the hands during longer use



Very well balanced

due to the special positioning of the gas cartridge



Smart

Computer-controlled intelligent ventilator adapts to the environment



Simple and fast adjustable tool nose




Removable

magazine footer



Laterally adjustable

device hook





LED display

prevents unexpected work interruptions in case the battery is low

Gas nailer FORCE ONE

Advantages, approvals and certificates



Suitable building materials



Versatile use in different base materials such as steel, concrete, solid bricks and limited in wood. Can be used on floors, walls and ceilings.

Applications

Electrical Installations

Fastening of various light electrical installations (cables, conduits, cable channels, lamp suspensions etc.)

HVAC sector

Fixing of heating pipes, ventilation channels etc.

Drywall construction

Fastening of drywall profiles

On the façade / tunnel construction / motorways

Fastening of insulating mats, moisture-repellent foils, protective material for floor coverings, fleece

Set includes

- 1 x Gas nailer FORCE ONE
- 1 x Safety glasses
- 2 x Ear plugs
- 2 x Battery
- 1 x Charger
- 1 x Carrying case
- 1 x Jam clear tool
- 1 x Instruction manual

FORCE ONE 2x Battery 1x Charger 1x Jam clear tool



Gas nailer FORCE ONE

Type	Art-No	[Set]	[pcs]
FORCE ONE with magazine for 20 nails	FONE20	1	–
FORCE ONE with magazine for 40 nails	FONE40	1	–



Battery and charger for gas nailer FORCE ONE

Type	Art-No	[pcs]	[pcs]
FORCE ONE Battery	FONEBAT	1	–
FORCE ONE Charger	FONECARSET	1	–



High-performance gas for gas nailer FORCE ONE

Type	Art-No	Height [mm]	Content [ml]	[pcs]	[pcs]
Fuel cell*	9GASFONE	180	80	1	20

* sufficient for min. 800 nails



Technical data of gas nailer FORCE ONE

Characteristics	Technical data
Height	365 mm
Width	124 mm
Length	334 mm
Weight	3.6 Kg (with battery included)
Loading capacity	FORCE ONE 20: 20 + 2 nails* FORCE ONE 40: 40 + 2 nails*
Type of battery	NiMH-battery (battery lasts for 4,500 nails)

Characteristics	Technical data
Capacity of battery	6V DC, 1.5Ah
Power consumption (Rated output)	8VA (10V 800mA)
Connection charger	100-240V AC. (50 or 60Hz)
Charging time	max. 120 minutes
Temperature range for use	-10°C to +40°C

* There must be at least 2 nails in the magazine, otherwise the nailer cannot be triggered.

Steel nails FORCE ONE XHA & TKA

Advantages



XHA premium nails for gas nailer FORCE ONE




TKA standard nails for gas nailer FORCE ONE

- XHA:
 - Premium nails; suitable for hard concrete and steel
 - Grooved nails to improve grip
- TKA: standard nails for concrete and solid bricks
- Each box includes one high-performance fuel cell, sufficient for 800 nails

Approvals and certificates



Mounting



XHA premium nails

+ each box includes one high-performance fuel cell



Type	Art-No	Nail-Ø $d_{s,N}$ [mm]	Length L [mm]	Head-Ø d_h [mm]	[pcs]	[pcs]
XHA premium nails 13 mm + Fuel cell	913800XHA	3	13	6,3	800	4.000
XHA premium nails 17 mm + Fuel cell	917800XHA	3	17	6,3	800	4.000
XHA premium nails 22 mm + Fuel cell	922800XHA	3	22	6,3	800	4.000
XHA premium nails 27 mm + Fuel cell	927800XHA	3	27	6,3	800	4.000
XHA premium nails 32 mm + Fuel cell	932800XHA	3	32	6,3	800	4.000
XHA premium nails 38 mm + Fuel cell	938800XHA	3	38	6,3	800	4.000




TKA standard nails

+ each box includes one high-performance fuel cell



Type	Art-No	Nail-Ø d _{s,N} [mm]	Length L [mm]	Head-Ø d _h [mm]	 [pcs]	 [pcs]
TKA nails 19 mm + Fuel cell	919800TKA	2,6	19	6,3	800	4.000
TKA nails 25 mm + Fuel cell	925800TKA	2,6	25	6,3	800	4.000

Overview - Suitable building materials for nails XHA and TKA

	XHA 13 mm	XHA 17 mm	TKA 19 mm	XHA 22 mm	TKA 25 mm	XHA 27 mm	XHA 32 mm	XHA 38 mm
								
 Steel	●							
 Concrete > C20/25		●		○				
 Concrete C20/25		○	●	●	●	○		
 Solid brick		○	●	●	●	●	○	
 Hollow brick					●	●	●	
 Wood								●

● very suitable

○ suitable to a limited extent

Overview over FORCE ONE accessories



Multidiameter nylon clamp Abranyl® ABT



Conduit clip FT



Pipe ring clip UT




Metal conduit clip PFT & DFT



Nylon clip for flat cables TPC & TPLC



Stud accessory ATR M6 & ATR M8



Wire conduit WSC & WDC



Rod hanger ATV



Cable tie fasteners TBB, TBBL, TBBD, TBM



Ceiling hanger AAT



Conduit clips FP & FPD



Metal washer AW



Compatibility FORCE ONE accessories with different gas nailers

CELO FORCE ONE Accessories		CELO		HILTI		POWERS	DEWALT		SPIT	WÜRTH
		FORCE ONE	AG II	GX-3	BX-3	TRAK IT® C3	TRAK IT® C5	DCN890	800E	DIGA CS2
										
ABT grey		✓	✓	✓	✓	✓	✓	✓	✓	✓
ABT black		✓	✓	✓	✓	✓	✓	✓	✓	✓
ABT white		✓	✓	✓	✓	✓	✓	✓	✓	✓
UT		✓	✓			✓			✓	
TPC		✓	✓			✓			✓	
TPLC		✓	✓			✓			✓	
WSC		✓	✓			✓			✓	
WDC		✓	✓			✓			✓	
TBB black FORCE ONE		✓	✓			✓			✓	
TBB grey FORCE ONE		✓	✓			✓			✓	
TBB grey				✓	✓	✓	✓	✓	✓	✓
TBBL black		✓	✓			✓			✓	
TBBL grey		✓	✓			✓			✓	
TBBD		✓	✓			✓			✓	
TBM		✓	✓			✓			✓	
FP		✓	✓	✓	✓	✓	✓	✓	✓	✓
FPD		✓	✓	✓	✓	✓	✓	✓	✓	✓
FT		✓	✓	✓	✓	✓	✓	✓	✓	✓
PFT		✓	✓	✓	✓	✓			✓	
DFT		✓	✓	✓	✓	✓			✓	
ATR M6		✓	✓			✓			✓	
ATR M8		✓	✓			✓			✓	
ATV 4, 5, 6		✓	✓			✓			✓	
ATV 8		✓	✓			✓			✓	
ATVS 8		✓	✓			✓			✓	
AAT		✓	✓			✓			✓	
AW		✓	✓			✓			✓	

FORCE ONE Accessories



Multidiameter nylon clamp Abranyl® ABT

Type Ø	Art-No	Art-No		Pipe-Ø				[pcs]	[pcs]
	grey	black	white	Metric [mm]	Copper [mm]	Steel [Inch]	Plastic [mm]		
ABT 14/18	918ABT	9418ABT	9118ABT	16	14-15-18	3/8"	16	100	600
ABT 20/25	925ABT	9425ABT	9125ABT	20-25	22	1/2"	20-25	50	450
ABT 25/32	932ABT	9432ABT	9132ABT	32	28	3/4"	32	50	300
ABT 35/42	942ABT	9442ABT	9142ABT	40	35-42	1"-1/4"	40-42	25	150




Pipe ring clip UT

Type	Art-No	Pipe-Ø Plastic [mm]	[pcs]	[pcs]
UT 16	916UT	16	100	900
UT 20	920UT	20	100	900
UT 25	925UT	25	100	900
UT 32	932UT	32	50	450
UT 40	940UT	40	50	300



Nylon clip for flat cables TPC, TPLC

Type	Art-No	For cable-Ø [mm]	Length L [mm]	Width W [mm]	Height H [mm]	[pcs]	[pcs]
TPC 6x17	9TPC	6x15	44,0	22,0	7,5	100	900
TPLC 9x25	9TPLC	9x25	64,5	30,0	10,5	100	900



Wire conduit WSC / WDC

Type	Art-No	Length L [mm]	Width W [mm]	Height H [mm]	 [pcs]	 [pcs]
WSC	9WSC	128	20	17	100	900
WDC	9WDC	232	20	17	50	450

Find our wide range of cable ties on our website at www.celofixings.com



Cable tie fasteners TBB for FORCE ONE

Type	Art-No	Height [mm]	Diameter Ø [mm]	 [pcs]	 [pcs]
TBB black	9TBB	13	27,5	100	1.200
TBB grey	9GRTBB	13	27,5	100	1.200



Cable tie fasteners TBB

Type	Art-No	Height [mm]	Diameter Ø [mm]	 [pcs]	 [pcs]
TBB grey	9NTBB	13	27,5	100	1.200



Cable tie fasteners TBBL

Type	Art-No	 [pcs]	 [pcs]
TBBL black	94TBBL	200	900
TBBL grey	9TBBL	200	900

Each box includes 200 pcs cable tie 4,8 x 288

FORCE ONE Accessories



Find our wide range of cable ties on our website at www.celofixings.com



Cable tie fasteners TBBT

Type	Art-No	Length L [mm]	Width W [mm]	Height H [mm]	[pcs]	[pcs]
TBBT	9TBBT	80,0	18,0	9,5	100	600



Cable tie fasteners TBM

Type	Art-No	Length L [mm]	Width W [mm]	Height H [mm]	Clearance hole Ø [mm]	[pcs]	[pcs]
TBM	9TBM	53	25	14	6	100	900



Conduit clips FPD

Type	Art-No	Copper [mm]	Pipe-Ø Steel [Inch]	Plastic [mm]	Pipe sizes [mm]	Length L [mm]	Width W [mm]	Height H [mm]	[pcs]	[pcs]
FPD 16	916FPD	18	3/8"	16	16 - 19	59	20	19,5	100	900
FPD 20	920FPD	22	1/2"	20	20 - 23	68	20	23,8	50	450
FPD 25	925FPD	28	3/4"	25	25 - 28	81	20	29	50	450



Conduit clips FP

Type	Art-No	Metric [mm]	Pipe-Ø			Length L [mm]	Width W [mm]	 [pcs]	 [pcs]
			Steel [Inch]	Copper [mm]	Plastic [mm]				
FP 16	916FP	16	–	–	16	41,5	23	100	900
FP 18	918FP	–	3/8"	18	–	43,5	23	100	900
FP 20	920FP	20	–	–	20	45,5	23	100	600
FP 22	922FP	–	1/2"	22	–	47,5	23	100	600
FP 25	925FP	25	–	–	25	50,5	23	100	600
FP 28	928FP	–	3/4"	28	–	53,5	23	100	600
FP 32	932FP	32	–	–	32	57,5	23	50	450



Conduit clip FT

Type	Art-No	Metric [mm]	Pipe-Ø			 [pcs]	 [pcs]
			Copper [mm]	Steel [inch]	Plastic [mm]		
FT 16	916FT	16	–	–	16	100	1.800
FT 18	918FT	–	18	3/8"	–	100	900
FT 20	920FT	20	–	–	20	100	900
FT 22	922FT	–	22	1/2"	–	100	900
FT 25	925FT	25	–	1/8"	25	100	900
FT 28	928FT	–	28	–	–	100	900
FT 32	932FT	–	–	–	32	100	900



Metal conduit clip PFT

Type	Art-No	Pipe-Ø		 [pcs]	 [pcs]
		Copper [mm]	Steel [Inch]		
PFT 5	95PFT	5	–	100	1.800
PFT 6	96PFT	6	–	100	1.800
PFT 7	97PFT	7	–	100	1.800
PFT 8	98PFT	8	–	100	1.800
PFT 10	910PFT	10	1/8"	100	1.800
PFT 12	912PFT	12	–	100	1.800
PFT 14	914PFT	14	–	100	900

FORCE ONE Accessories



Metal conduit clip DFT

Type	Art-No	Pipe-Ø		 [pcs]	 [pcs]
		Copper [mm]	Steel [Inch]		
DFT 5	95DFT	5	–	100	1.800
DFT 6	96DFT	6	–	100	1.800
DFT 7	97DFT	7	–	100	1.800
DFT 8	98DFT	8	–	100	900
DFT 10	910DFT	10	1/8"	100	900
DFT 12	912DFT	12	–	100	900



Stud accessory ATR

Type	Art-No	Dimensions Thread x Length	Number of fixing points	 [pcs]	 [pcs]
ATR 6	9TR6	M6x6,5	1	100	900
ATR 8C	9TR8C	M8x10	2	100	900
ATR 8L	9TR8L	M8x16	2	100	900




Rod hanger ATV, ATVS

Type	Art-No	Metric thread	 [pcs]	 [pcs]
ATV4	9TV4	M4	100	600
ATV5	9TV5	M5	100	600
ATV6	9TV6	M6	100	600
ATV8	9TV8	M8	50	450
ATVS8	9TVS8	M8	50	450



Ceiling hanger AAT

Type	Art-No	Height H [mm]	Length L [mm]	Width W [mm]	 [pcs]	 [pcs]
AAT	9AAT	27	26	19	100	900



Metal washer AW

Type	Art-No	Diameter Ø [mm]	 [pcs]	 [pcs]
AW 15	915AW	15	200	3.600
AW 25	925AW	25	200	3.600



Punched metal tape Cintapolo CA

Type	Art-No	Width W [mm]	Clearance hole-Ø d _i [mm]	Distance of holes S [mm]	Tensional strength ≤ [kg]	 [Stück]	 [Stück]
Cintapolo 12	12CA	12	5,1	14	50	10	-
Cintapolo 17	CA	17	7	20	95	10	-



CELO Befestigungssysteme GmbH
Industriestraße 6
D-86551 Aichach
www.celofixings.com
Hotline: +49 (0) 8251-90485-0
Telefax: +49 (0) 8251-90485-49
E-mail: info@celofixings.de

Small Things Matter

Presented by:

EN 10/20

Technical products and illustrations are subject to change. The reprint of this brochure, in part or in whole, is prohibited.
CELO Befestigungssysteme GmbH accepts no liability for the correctness of the information provided.