

**DECLARATION OF PERFORMANCE (DoP)**  
according to Construction Products Regulation (CPR) No 305/2011

**DoPNo. 13/0372a(2012) - en**

1. Unique identification code of the product-type: **Drop in anchor SA plus**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**ETA-13/0372(from 15.12.2020), annex 1**  
**Batch number: see packaging of the product.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

<b>Generic type</b>	Way controlled expansion anchor
<b>For use in</b>	Non-cracked concrete C20/25 – C50/60 (EN206:2013 + A1:2016) covered sizes: M8, M10, M12 and M16
<b>Option / Category</b>	7
<b>Loading</b>	Static and quasi-static
<b>Material</b>	<u>Zinc-plated steel:</u> dry internal conditions only covered sizes: M8, M10, M12 and M16
<b>Temperature range if applicable</b>	-

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**CELO Befestigungssysteme GmbH**  
**Industriestrasse 6**  
**86551 Aichach, Germany**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **system 1**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
**Deutsches Institut für Bautechnik (DIBt), Berlin**

issued:

**ETA-13/0372(from 15.12.2020)**

on the basis of

**EAD 330232-00-0601, Edition 10/2016**

The notified body **0672** performed under **system 1**:

- **initial type testing of the product,**
- **initial inspection of factory and of factory production control,**
- **continuous surveillance, assessment and approval of factory production control.**

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
Characteristic resistance for tension	TR 055, Edition 2018 oder EN 1992-4:2018	ETA-13/0372(2012), annex C1	EAD 330232-00-0601, Edition 10/2016
Characteristic resistance for shear	TR 055, Edition 2018 oder EN 1992-4:2018	ETA-13/0372(2012), annex C2	
Minimum spacing and minimum edge distance	TR 055, Edition 2018 oder EN 1992-4:2018	ETA-13/0372(2012), annex B2	
Displacement for serviceability limit state	TR 055, Edition 2018 oder EN 1992-4:2018	ETA-13/0372(2012), annex C3	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Achim Ruppertz**  
Marketing and Technical Manager

**Aichach, 20.12.2020**

